Effective August 2011 Supersedes March 2008 Model CVX050 Model CVX100

CVX surge protective device



Contents

Description F	Page
Product application	1
General description	2
Features, functions, and benefits	2
Optional features	2
Standards and certifications	2
Product specifications	3
Product ordering guidelines.	4

Product application

Eaton's CVX050 and CVX100 surge protective devices (SPDs) protect electronic equipment from damaging transients. These units are suitable for medium and low exposure level applications that require cost-effective, high quality system protection including:

- Residential/small business
- Light industrial
- Light commercial
- · Service entrance and branch panel protection
- · OEM applications
- Control panels



General description



CVX050/100

With over two decades of experience in the surge suppression industry and extensive R&D initiatives, Eaton is considered a world leader in SPD manufacturing. All of Eaton's products are manufactured in an ISO 9001:2000 and ISO 14001 certified facility.

Eaton's CVX050/100 models are rugged, cost-effective, high-quality SPDs that feature self-protected metal oxide varistors (MOVs) that eliminate the failure characteristics of standard metal-oxide-varistors. The self-protected MOV is a fail-safe device that monitors the status of the metal-oxide disk and disconnects itself from the power system when the disk is approaching breakdown.

The CVX050/100 is easy to install adjacent or even internal to electrical equipment. When installing an SPD in a retrofit environment, it is important to mount the device as close to the electrical equipment as possible. Keep the wiring (lead length) between the electrical equipment and SPD as short as possible, and twist or wire tie the conductors together to reduce the wire's impedance factor.

Features, functions, and benefits

- Large diameter, self-protected metal oxide varistors provide long life and fail-safe operation
- Rated 50 kA (CVX050) or 100 kA (CVX100) peak surge current
- Wide range of voltage applications from 100 to 600 Vac
- Rugged NEMA® 4X (IP56) enclosure
- LED monitoring of each phase
- Wiring systems: Single-phase, split-phase, three-phase wye, three-phase delta or three-phase high leg delta
- #10 AWG (6mm²) stranded wire included
- 34-inch threaded conduit fitting included
- 5 year free-replacement warranty

Optional features

· Available external mounting feet

Standards and certifications

- UL® 1449 3rd Edition for surge suppression devices
- CSA[®] and CE marked
- Vibration tested to IEC 60255-21-1 and IEC 60255-21-2



Figure 1. Standard Dimensions

Product specifications

Table 1. CVX050/100 Model Specifications

Description	Specification					
Peak kA per phase	50, 100					
Peak kA per mode	50					
Nominal discharge current	20 kA ①					
Short-circuit current rating	100 kA					
Single-phase voltages	200, 208, 220, 230, 240, 277, 380, 400, 440, 460, 480					
Split-phase voltages	100/200, 110/220/ 120/240					
High leg delta voltages	240					
Wye system voltages	100/175, 110/190, 120/208, 127/220, 220/380, 230/400, 240/415, 277/480, 305/525, 347/600					
Delta system voltages	200, 208, 220, 230, 240, 380, 400, 415, 440, 480, 525, 600					
Input power frequency	47–420 Hz (50/60 Hz typical)					
Protection modes	Single-phase: L-N, N-G, L-G Split-phase: L-N, N-G, L-G, L-L High leg delta: L-N, N-G, L-G, L-L, H-N, H-G, H-L Wye: L-N, N-G, L-G, L-L Delta: L-G, L-L					
Number of ports	1					
Specific energy	100 kJ/0hm					
Weight	≈2.0 lbs (1.0 kg)					
Operating temperature	-13°F (-25°C) to +140°F (+60°C)					
Vibration tested	IEC 60255-21-1 and IEC 60255-21-2					

① 480L, 600D, and 600Y units rated 10 kA In.

Table 2. CVX050/100 Voltage Ratings

	Evetern	Nominal	MCOV				UL 1449-3 VPR ()			
Model	Configuration	System Voltage	L-L	L-N	L-G	N-G	L-L	L-N	L-G	N-G
CVX050										
230L	Single-phase two-wire + ground	200, 208, 220, 230, 240, 277	_	320	640	320	_	1200	1200	1200
480L	Single-phase two-wire + ground	380, 400, 440, 460, 480		550	1100	550	_	1800	4000	1800
240S	Split-phase three-wire + ground	100/200, 110/220, 120/240	300	150	300	150	1200	700	1200	800
208Y	Three-phase wye (star) four-wire + ground	100/175, 110/190, 120/208, 127/220	300	150	300	150	1200	700	1200	800
480Y	Three-phase wye (star) four-wire + ground	220/380, 230/400, 240/415, 277/480	640	320	640	320	2500	1200	2000	1200
600Y	Three-phase wye (star) four-wire + ground	305/525, 347/600	840	420	840	420	2500	1500	2500	1500
240D	Three-phase delta three-wire + ground	200, 208, 220, 230, 240	640	_	320	_	2000	_	1200	_
240H	Three-phase high leg delta	240	300	150	150	640	1500	700	1200	700
480D	Three-phase delta three-wire + ground	380, 400, 415, 440, 480	1100	_	550	_	3000	_	1800	_
600D	Three-phase delta three-wire + ground	525, 600	1100	_	700	_	3000	_	2500	_
CVX100										
230L	Single-phase two-wire + ground	200, 208, 220, 230, 240, 277	_	320	320	320	_	1200	1200	1200
480L	Single-phase two-wire + ground	380, 400, 440, 460, 480	—	550	550	550	—	1800	1800	1800
240S	Split-phase three-wire + ground	100/200, 110/220, 120/240	300	150	150	150	1200	700	800	700
208Y	Three-phase wye (star) four-wire + ground	100/175, 110/190, 120/208, 127/220	300	150	150	150	1000	600	700	700
480Y	Three-phase wye (star) four-wire + ground	220/380, 230/400, 240/415, 277/480	640	320	320	320	1800	1200	1200	1200
600Y	Three-phase wye (star) four-wire + ground	305/525, 347/600	840	420	420	420	2500	1500	1500	1500
240D	Three-phase delta three-wire + ground	200, 208, 220, 230, 240	640	_	320	_	1800	_	1200	_
240H	Three-phase high leg delta	240	300	150	150	150	1200	700	700	700
480D	Three-phase delta three-wire + ground	380, 400, 415, 440, 480	1100		550		3000	_	1800	_

① UL 1449 3rd Edition VPR (voltage protection rating) test environment: All tests performed with 6-inch lead length, positive polarity.

Technical Data **TD01005002E** Effective August 2011

Product ordering guidelines



CVX050/100 accessories

Table 3. CVX050/100 Accessories

Description	Catalog Number
External mounting feet	MNTGFTX



Figure 2. Wall Mounting with External Mounting Feet

Eaton Corporation Electrical Sector

Electrical Sector 1111 Superior Ave. Cleveland, OH 44114 United States 877-ETN-CARE (877-386-2273) Eaton.com



© 2011 Eaton Corporation All Rights Reserved Printed in USA Publication No. TD01005002E / Z11434 August 2011

Eaton is a registered trademark of Eaton Corporation.

All other trademarks are property of their respective owners.